

Benchtop Ratio Turbidimeter

BEP-TB40A BEP-TB20A BEP-TB10A
BEP-TB5A BEP-TB2A BEP-TB1A

Description

- Turbidimeter is an instrument used to measure the degree of scattering and attenuation of light generated by insoluble particulate matter suspended in water (or transparent liquid), and can quantitatively characterize the content of these suspended particulate matter. It is widely used in waterworks, food, chemical industry, power plant, metallurgy, environmental protection, beverage, wine making, pharmaceutical industry and other departments. And it is a commonly used laboratory instrument.



Features



- Adopting microcomputer technology, color LCD touch screen display, the operation is more intuitive and convenient.



- With average measurement function; 1000 sets of test data can be stored, and the data can be saved, printed, and uploaded.



- With time and date setting function, USB communication interface and U disk to read data, support to connect to PC for data upload.

- Adopting scattered-transmitted light measuring principle, ratio calibration.
- Automatic range switching, supporting multi-point calibration

Characteristics

- Measurement of light scatter and decay of the insoluble particles suspended in water or transparent liquids;
- Quantitative analysis of particle contents.

Specifications

Model	BEP-TB40A	BEP-TB20A	BEP-TB10A	BEP-TB5A	BEP-TB2A	BEP-TB1A
Light source	Tungsten halogen lamp 6V, 10W					
Receiving element	Silicon photocell					
Measuring mode	NTU, FTU, EBC, ASBC					
Measurement range NTU	0.00~50.0; 50.1~200; 200.1~2000; 2000.1~4000 (automatic range switchover)	0.00~50.0; 50.1~200; 200.1~2000 (automatic range switchover)	0.00~50.0; 50.1~200; 200.1~1000 (automatic range switchover)	0.00~50.0; 50.1~200; 200.1~500 (automatic range switchover)	0.00~50.0; 50.1~200 (automatic range switchover)	0.00~50.0; 50.1~100 (automatic range switchover)
Readings display	LCD touch screen					
Minimum reading	0.001					
Allowable error of indication	≤±6%					
Zero Drift	≤±0.3%FS					
Stability of indication	≤±1%FS					
Repeatability	≤0.5%					
Sample bottle	Φ25mm×95mm					
Data storage	1000 sets					
Calibration modes	7	6	5	4	3	3
Sample volume	30~40mL					
Interface	USB/U disk					
Weight (Gross)	7.5 kg	9				
Overall dimensions	430mm×430mm×320mm					

Benchtop Ratio Turbidimeter

- USB flash drive 1
- Power cable 1
- USB cable 1
- 3 small bottles (BEP-TB1A BEP-TB2A BEP-TB5A)
- 5 small bottles (BEP-TB40A BEP-TB20A BEP-TB10A)

- Shade cover 1
- User manual 1
- Packing list 1



Portable Turbidity Meter

BEP-TB20B BEP-TB10B BEP-TB5B BEP-TB2B
BEP-TB1B BEP-TB50 BEP-TB20

- 

Accuracy: $\pm 6\%$
- 

Data storage: 2000 sets
- 

Unit switches: NTU, FTU, EBC, ASBC
- 

Measurement range NTU: 0.00~2000; 0.00~1000;
0.00~500; 0.00~200; 0.00~100; 0.00~50; 0.00~20.0



Features




- LCD, backlight can be set



- Novel appearance, convenient for user in field testing



- Automatic range switchover, supporting zero-point and four-point calibration, in line with GLP Regulation



- Using four AA batteries, external power supply, automatic power off function

Turbidity Meters

- Vial 5

5AA battery 4

USB communication cable 1
- User manual 1

Packing list 1

Test report 1

Specifications

Model	BEP-TB20B	BEP-TB10B	BEP-TB5B	BEP-TB2B
Light source	LED; 860nm (Wavelength)			
Unit switches	NTU, FTU, EBC, ASBC			
Measurement range NTU	0.00~20.0; 20.01~200; 200.1~2000	0.00~20.0; 20.01~200; 200.1~1000	0.00~20.0; 20.01~200; 200.1~500	0.00~20.0; 20.01~200
Readings display	LCD			
Minimum reading	0.001			
Allowable error of indication	$\pm 6\%$			
Zero Drift	$\pm 0.5\%$ FS			
Stability of indication	$\pm 0.5\%$ FS			
Repeatability	$\leq 0.5\%$			
Sample bottle	$\Phi 25\text{mm} \times 65\text{mm}$			
Sample volume	20~25mL			
Interface	USB			
Data storage	2000 sets			
Calibration modes	7	6	5	4
G.W.(kg)	3kg			
Package Dimension(W*D*H)	390×290×280mm			

Model	BEP-TB1B	BEP-TB50	BEP-TB20
Light source	LED; 860nm (Wavelength)		
Unit switches	NTU, FTU, EBC, ASBC		
Measurement range NTU	0.00~20.0; 20.01~100	0.00~20.0; 20.01~50	0.00~20.0
Readings display	LCD		
Minimum reading	0.001		
Allowable error of indication	$\pm 6\%$		
Zero Drift	$\pm 0.5\%$ FS		
Stability of indication	$\pm 0.5\%$ FS		
Repeatability	$\leq 0.5\%$		
Sample bottle	$\Phi 25\text{mm} \times 65\text{mm}$		
Sample volume	20~25mL		
Interface	USB		
Data storage	2000 sets		
Calibration modes	4	3	2
G.W.(kg)	3kg		
Package Dimension(W*D*H)	390×290×280mm		

Portable Turbidity Meter

BEP-TB100



Advantages

- High-performance portable turbidity meter meets the design criteria in ISO 7027
- 2 to 5 points calibration using the Formazin Standards
- Selectable 4 turbidity units, including the NTU, FNU, EBC and ASBC
- Single measurement mode automatically senses and locks a stable reading
- Continuous measurement mode can be used for indexing or matching the sample vials
- Auto-Power Off effectively conserves battery life
- Setup menu allows to set the number of calibration points, resolution, date and time, etc.
- Reset function automatically resumes all settings back to the factory defaults
- Expanded memory stores or recalls up to 100 data sets
- USB communication interface for data transfer or connecting a power adapter to meter

BEP-TB100 Turbidity Meter
Turbidity standard solution (0.02, 200, 500, 1000 NTU)
Sample bottles (2 pieces)
Lint free fabric
AA battery
Carrying case

Specifications

Model		BEP-TB100
Turbidity	Principle	ISO 7027 nephelometric method (90°)
	Turbidity Unit	NTU, FNU, EBC, ASBC
	Range	0~1100NTU, 0~275 EBC, 0~9999ASBC
	Resolution	0.01 (0~99NTU), 0.1 (100~999NTU), 1 (1000~1100NTU)
	Accuracy	±2% of reading (0~500NTU), ±3% of reading (501~1100NTU)
	Calibration Points	2 to 5 points
	Calibration Standards	0.02, 10, 200, 500, 1000NTU
Other Specifications	Light Source	Infrared-emitting diode (850nm wavelength)
	Detector	Silicon photo diode
	Stray Light	<0.02 NTU
	Sample Vial	60(H)× 25 (Dia)mm
	Sample Volume	30mL
	Memory	100 data sets
	Communication Interface	USB
	Operating Temperature	0-50 ℃
	Display	Custom LCD (60×40mm)
	Power Requirements	3×1.5V AA batteries or DC5V power adapter
	Dimensions	180 (L)× 85 (W)×70 (H)mm
	Weight	300g



Ordering Information

BEP-TB100: Meter, turbidity standards (0.02, 200, 500, 1000 NTU), sample vials, lint-free cloth and carrying case

Benchtop Turbidity Meter

BEP-TB200



Features

- 2 to 7 points calibration using the Formazin Standards
- Selectable 4 turbidity units, including the NTU, FNU, EBC and ASBC etc.
- Reset function automatically resumes all settings back to the factory defaults
- Expanded memory stores or recalls up to 200 data sets
- Turbidity, total suspended solids (TSS)
- TSS conversion factor ensures the accurate measurement of the total suspended solids
- Auto-Read function senses and locks a stable reading
- Setup menu allows to set the date and time, measurement mode, resolution,
- Password protection prevents the unauthorized calibration and settings
- USB communication interface is easy to transfer data to PC



BEP-TB200 Turbidity Meter

- Turbidity standard solution (0.02, 200, 500, 1000 NTU)
- Sample bottles (2 pieces)
- Lint free fabric
- DC12V power adapter



- Measurement Parameters**
- Turbidity, total suspended solids (TSS)

Specifications

Model		BEP-TB200
Turbidity	Range	0~2000NTU, 0~500 EBC, 0~9999ASBC
	Turbidity Unit	NTU, FNU, EBC, ASBC
	Resolution	0.01 (0~99NTU), 0.1 (100~999NTU), 1 (1000~2000NTU)
	Accuracy	±2% of reading (0~500NTU), ±3% of reading (501~2000NTU)
	Calibration Points	2to7 points
	Calibration Standards	0.02, 10, 200, 500, 1000, 1500, 2000NTU
TSS	Range	Depending on the TSS conversion factor
	Accuracy	3% of reading
Other Specifications	light Source	Infrared-emitting diode (850nm wavelength)
	Detector	Silicon photo diode
	Stray Light	<0.02 NTU
	tray Light	60(H)× 25 (Dia)mm
	Memory	200 data sets
	Communication Interface	USB
	Operating Temperature	0~50°C
	Display	4.5 inches TFT LCD
	Power Requirements	DC12V power adapter
	Dimensions	250 (L)× 177 (W)×96(H)mm
	Weight	1.2kg



Ordering Information

BEP-TB200: Meter, turbidity standards (0.02, 200, 500, 1000 NTU), sample vials, lint-free cloth and power adapter